EasyMatch® QC Quick Start Guide

A60-1017-602 ver.1.0







ense	C Restart EasyMatch QC
C Icon rt menu, open	 When the acknowledgement page has been shown, press OK to restart EasyMatch QC.
Lab >	EasyMatchQC ×
ctivate	
/ed as EZMQC	Figure 6. Restart EasyMatch QC
e before	D Install the HunterLab Sensor.
xtion. ation iquely or ided d with	 Upon re-start, the following message will be displayed: 'Sensor not yet installed'. Connect the sensor to the computer using the cable provided. The Setup Sensor screen allows selection of the instrument model and the communications port. To continue select Add Sensor. Select OK when ready.
a with nail from istration/	Serici Monger Extent Series Type
	Figure 7. Sensor Manager
n ID m the	2. The next screen sets up the communication port. Select Next when ready. Setup Second Type Intelling Your Short Type Intelling Your Your Your Your Your Your Your Your
n page	Figure 8, Type 8, Port Selection
nse Key ID be vation	3. Note: The sensor must match the SoftKey License. If a sensor mismatch error occurs, please
uired to with Key ID.	or contact HunterLab to obtain a license to match the sensor to be connected.
ne Soffkey numb	SENSOR-1 X Sensor Mismatch.Please connect licensed sensor.
the	ОК
oort.	Figure 9. Sensor Mismatch
kl). SoftKey	F Standardize

1. Select the option next to Standardize Now to proceed immediately to standardization upon completion of sensor configuration.

For more detailed instructions on using the instrument, please refer to the EasyMatch® QC User's Manual.

MatchQC

Actuate

Visit www.hunterlab.com for information on all our products.

